



Soft PVC hose with embedded reduced pitch galvanised steel spiral for suction and delivery of food liquids.



SMOOTH SURFACES



FLEXIBILITY



ABRASION RESISTANCE



TEMPERATURE RANGE

-5°C +65°C
23°F +149°F



CHEMICAL RESISTANCE

PVC table



CRUSHING RESISTANCE



FOR FOOD

Suitable according to Reg. CE 1935/2004 and Reg. UE 10/2011 for contact with foodstuff that requires a simulating liquid type A B C, migration tests performed at 40°C for 24 hours.

Ø I.D.	Ø I.D.	Ø O.D.	TOTAL THICKNESS	WEIGHT	BENDING RADIUS	WORKING PRESSURE 1:3 23°C	BURSTING PRESSURE 23°C	VACUUM 23°C	SPIRAL PITCH	SPIRAL DIRECTION	Ø SPIRAL	COIL LENGTH	AVAILABILITY
inch	mm	mm	mm	g/m	mm	bar	bar	m h2o	mm		mm	m	
3/8	10	15.5	2.75	160	20	10	30	9	4	right	0.7	60	IN STOCK
	12	17.5	2.75	185	25	10	30	9	4.5	right	0.7	60	IN STOCK
	14	20	3	235	30	8	24	9	5	right	0.8	60	IN STOCK
5/8	16	22	3	255	35	8	24	9	5	right	0.8	60	IN STOCK
	17	23	3	265	38	7	21	9	5.5	right	0.8	60	ON DEMAND
	18	24	3	275	40	7	21	9	5.5	right	0.8	60	IN STOCK
	20	26	3	330	50	6	18	9	5.5	right	0.8	60	IN STOCK
1	25	33.5	4.25	530	60	5	15	9	8	right	1.2	60	IN STOCK
	30	38.5	4.25	620	70	5	15	9	8.5	right	1.2	60	IN STOCK
1 1/4	32	40.5	4.25	650	75	5	15	9	8.5	right	1.2	60	IN STOCK
	35	44	4.5	770	80	4.5	13.5	9	9	right	1.4	60	IN STOCK
1 1/2	38	47	4.5	810	90	4	12	9	9.5	right	1.4	30	IN STOCK
	40	49.5	4.75	880	95	4	12	9	9.5	right	1.4	30	IN STOCK
1 3/4	45	55	5	1100	110	3.5	10.5	9	10	right	1.6	30	IN STOCK
	50	61	5.5	1270	125	3.5	10.5	9	10.5	right	1.6	30	IN STOCK
2	60	72	6	1700	140	3	9	9	11	right	1.6	30	IN STOCK
	63	75	6	1770	150	3	9	9	12	right	1.6	30	IN STOCK
	75	88	6.5	2300	200	2	6	9	13	right	2	30	IN STOCK
2 1/2	80	94	7	2600	220	2	6	9	14	right	2	30	IN STOCK
	90	104	7	3000	260	2	6	9	16	right	2.5	30	IN STOCK
	100	114	7	3350	300	2	6	9	17	right	2.5	30	IN STOCK

All technical specifications apply to a temperature of 23°C ± 2°C (ISO 291). - Tolerance on all specifications ± 5%.