

PTFE slang glad

TUBING



TECHNISCHE GEGEVENS BIJ 20°C

Inwendig:	PTFE GLAD
Inlagen:	-
Uitwendig:	-
Temperatuurbestendigheid:	-70°C +260°C
Rollengte:	50 / 100 meter
Normen:	-
Opdruk:	-
Opmerkingen:	Ook leverbaar in zwarte antistatische uitvoering

Art.code	Inwendig MM*	Uitwendig MM*	WD BAR	BD BAR	Rollengte
10003001003050	1	3	30	105	50
10003001003100	1	3	30	105	100
10003002004050	2	4	23	80	50
10003002004100	2	4	23	80	100
10003003005050	3	5	18	63	50
10003003005100	3	5	18	63	100
10003004006050	4	6	15	52	50
10003004006100	4	6	15	52	100
10003005007050	5	7	13	45	50
10003005007100	5	7	13	45	100
10003005008050	5	8	18	63	50
10003005008100	5	8	18	63	100
10003006008050	6	8	11	38	50
10003006008100	6	8	11	38	100
10003008010050	8	10	9	31	50
10003008010100	8	10	9	31	100
10003009012050	9	12	12	42	50
10003009012100	9	12	12	42	100
10003010012050	10	12	8	28	50
10003010012100	10	12	8	28	100
10003012014050	12	14	7	24	50
10003012014100	12	14	7	24	100
10003014016050	14	16	6	21	50
10003016018050	16	18	5	17	50
10003018020050	18	20	5	17	50
10003020022050	20	22	4	14	50
10003022025035	22	25	6	21	35
10003025028033	25	28	5	17	33

* Opgegeven maten zijn onderhevig aan toleranties.

