

# PTFE slang glad

## TUBING



### TECHNISCHE GEGEVENS BIJ 20°C

<b>Inwendig:</b>	PTFE GLAD
<b>Inlagen:</b>	-
<b>Uitwendig:</b>	-
<b>Temperatuurbestendigheid:</b>	-70°C +260°C
<b>Rollengte:</b>	50 / 100 meter
<b>Normen:</b>	-
<b>Opdruk:</b>	-
<b>Opmerkingen:</b>	Voedingsmiddelengeslacht

Art.code	Inwendig MM*	Uitwendig MM*	WD BAR	BD BAR	Rollengte meter
10003002003050	2	3	8	32	50
10003002003100	2	3	8	32	100
10003002004050	2	4	24	96	50
10003002004100	2	4	24	96	100
10003003004050	3	4	9	36	50
10003003004100	3	4	9	36	100
10003003005050	3	5	18	72	50
10003003005100	3	5	18	72	100
10003004005050	4	5	7	28	50
10003004005100	4	5	7	28	100
10003004006050	4	6	13	52	50
10003004006100	4	6	13	52	100
10003004008050	4	8	22	88	50
10003004008100	4	8	22	88	100
10003005006050	5	6	5	20	50
10003005006100	5	6	5	20	100
10003005007050	5	7	11	44	50
10003005007100	5	7	11	44	100
10003006008050	6	8	9	36	50
10003006008100	6	8	9	36	100
10003006009050	6	9	12	48	50
10003006009100	6	9	12	48	100
10003007009050	7	9	7	28	50
10003007009100	7	9	7	28	100
10003007010050	7	10	10	40	50
10003007010100	7	10	10	40	100
10003008010050	8	10	6	24	50
10003008010100	8	10	6	24	100
10003009012050	9	12	7	28	50
10003009012100	9	12	7	28	100

\* Opgegeven maten zijn onderhevig aan toleranties.



# PTFE slang glad

## TUBING



### TECHNISCHE GEGEVENS BIJ 20°C

<b>Inwendig:</b>	PTFE GLAD
<b>Inlagen:</b>	-
<b>Uitwendig:</b>	-
<b>Temperatuurbestendigheid:</b>	-70°C +260°C
<b>Rollengte:</b>	50 / 100 meter
<b>Normen:</b>	-
<b>Opdruk:</b>	-
<b>Opmerkingen:</b>	Voedingsmiddelengeschikt

Art.code	Inwendig MM*	Uitwendig MM*	WD BAR	BD BAR	Rollengte meter
10003010012050	10	12	5	20	50
10003010012100	10	12	5	20	100
10003010014050	10	14	10	40	50
10003010014100	10	14	10	40	100
10003012014050	12	14	8	32	50
10003012014100	12	14	8	32	100
10003014016050	14	16	4	16	50
10003014016100	14	16	4	16	100
10003016018050	16	18	3	12	50
10003018020050	18	20	3	12	50
10003019022050	19	22	4	16	50
10003020022050	20	22	3	12	50

\* Opgegeven maten zijn onderhevig aan toleranties.

